



Infotrend EonStor DS Expansion Enclosures



Through SAS expansion ports, each EonStor DS storage system can connect with robust and high-density expansion enclosures to provide a maximum capacity of 240 drives. The incremental approach provided by EonStor DS capacity scaling effectively satisfies growing application needs while reducing wasted upfront investments.

Technical Specifications 2.5-inch SAS Drives

	ESDS B12S-J2000-R	ESDS B12S-J2000-G
Controller	Dual redundant	Single
Host Connectivity	Two (2) 6Gb/s SAS 4x wide ports per controller	
Drive Connectivity	6Gb/s SAS	
Drive Bays	12	
Corresponding EonStor DS Models¹	ESDS B12F-R2840 ESDS B12S-R2240 ESDS B12E-R2140	ESDS B12F-G2840 ESDS B12S-G2240 ESDS B12E-G2140
Power Supplies	Two redundant 380W	Two redundant 250W
Form Factor²	1U, 19-inch rackmount	
Service and Support³		
Standard Service	3-year limited hardware warranty and 8x5 phone, web and email support	
Upgrade/Extension Options	Replacement part dispatch on the next business day (up to 5 years) Advanced Service: 24x7 phone, web and email support + onsite diagnostics on the next business day (up to 5 years) Premium Service: 24x7 phone, web and email support + onsite diagnostics in 4 hours (up to 5 years) Extended Standard Service up to 5 years	

Technical Specifications 2.5-inch SAS Drives

	ESDS B24S-J2000-R	ESDS B24S-J2000-S
Controller	Dual redundant	Single
Host Connectivity	Two (2) 6Gb/s SAS 4x wide ports per controller	
Drive Connectivity	6Gb/s SAS	
Drive Bays	24	
Corresponding EonStor DS Models¹	ESDS B24F-R2842 ESDS B24F-R2840 ESDS B24S-R2242 ESDS B24S-R2240 ESDS B24E-R2142	ESDS B24F-G2842 ESDS B24F-G2840 ESDS B24S-G2242 ESDS B24S-G2240 ESDS B24E-G2142
Power Supplies	Two redundant 530W	
Form Factor²	2U, 19-inch rackmount	
Service and Support³		
Standard Service	3-year limited hardware warranty and 8x5 phone, web and email support	
Upgrade/Extension Options	Replacement part dispatch on the next business day (up to 5 years) Advanced Service: 24x7 phone, web and email support + onsite diagnostics on the next business day (up to 5 years) Premium Service: 24x7 phone, web and email support + onsite diagnostics in 4 hours (up to 5 years) Extended Standard Service up to 5 years	

1. Please refer to corresponding models for the supported drives of expansion enclosures.
 2. For detailed dimensions, please visit the Infotrend website.
 3. All EonStor DS systems are shipped with Standard Service.

Technical Specifications

3.5-inch 6Gb/s SAS Drives

	ESDS S16S-J2000-R	ESDS S16S-J2000-S	ESDS S12S-J2000-R	ESDS S12S-J2000-G
Controller	Dual redundant	Single	Dual redundant	Single
Host Connectivity	Two (2) 6Gb/s SAS 4x wide ports per controller			
Drive Connectivity	6Gb/s SAS			
Drive Bays	16	16	12	12
Corresponding EonStor DS Models¹	ESDS S24F-R2851 ESDS S24F-R2840 ESDS S16F-R2852-6 ESDS S16F-R2851 ESDS S16F-R2842 ESDS S16F-R2840 ESDS S16S-R2240 ESDS S16S-R2240-4 ESDS S16E-G2152-6 ESDS S16E-R2251 ESDS S16E-R2240 ESDS S16E-R2142 ESDS S16S-R2250 ESDS B24F-R2842 ESDS B24F-R2840 ESDS B24S-R2242 ESDS B24S-R2240 ESDS B24E-R2142 ESDS B12F-R2840 ESDS B12S-R2240 ESDS B12E-R2140	ESDS S24F-G2851 ESDS S24F-G2840 ESDS S24S-G2240 ESDS S24S-G2240-4 ESDS S24E-G2142 ESDS S16F-G2852-6 ESDS S16F-G2851 ESDS S16F-G2842 ESDS S16F-G2840 ESDS S16S-G2240 ESDS S16S-G2240-4 ESDS S16E-G2152-6 ESDS S16E-G2251 ESDS S16E-G2240 ESDS S16E-G2142 ESDS S16S-G2250 ESDS B24F-G2842 ESDS B24F-G2840 ESDS B24S-R2242 ESDS B24S-R2240 ESDS B24E-G2142 ESDS B24E-G2240 ESDS B12F-G2840 ESDS B12S-G2240 ESDS B12E-G2140	ESDS S12F-R2851 ESDS S12F-R2840 ESDS S12S-R2240 ESDS S12S-R2240-4 ESDS S12E-R2251 ESDS S12E-R2140 ESDS B24F-R2842 ESDS B24F-R2840 ESDS B24S-R2242 ESDS B24S-R2240 ESDS B24E-R2142 ESDS B12F-R2840 ESDS B12S-R2240 ESDS B12E-R2140	ESDS S12F-G2851 ESDS S12F-G2840 ESDS S12S-G2240 ESDS S12S-G2240-4 ESDS S12E-G2251 ESDS S12E-G2140 ESDS B24F-G2842 ESDS B24F-G2840 ESDS B24S-G2242 ESDS B24S-G2240 ESDS B24E-G2142 ESDS B12F-G2840 ESDS B12S-G2240 ESDS B12E-G2140
Power Supplies	Two redundant 530W	Two redundant 530W	Two redundant 530W	Two redundant 350W
Form Factor²	3U, 19-inch rackmount	3U, 19-inch rackmount	2U, 19-inch rackmount	2U, 19-inch rackmount

Technical Specifications

3.5-inch 6Gb/s SAS Drives

	ESDS S48S-J2000-R	ESDS S48S-J2000-G
Controller	Dual redundant	Single
Host Connectivity	Two (2) 6Gb/s SAS 4x wide ports per controller	
Drive Connectivity	6Gb/s SAS	
Drive Bays	48	48
Corresponding EonStor DS Models¹	ESDS S48F-R2842 ESDS S24F-R2851 ESDS S16F-R2852-6 ESDS S16F-R2851 ESDS S12F-R2851 ESDS S12E-R2251 ESDS S16E-2152-6 ESDS S16E-R2251 ESDS S16S-R2250	ESDS S48F-G2842 ESDS S24F-G2851 ESDS S16F-G2852-6 ESDS S16F-G2851 ESDS S12F-G2851 ESDS S12E-G2251 ESDS S16E-G2152-6 ESDS S16E-G2251 ESDS S16S-G2250
Power Supplies	2+1 redundant 530W power supplies	
Form Factor²	4U, 19-inch rackmount / 445mm (W) x 175.9mm (H) x 873.5mm (D)	
Service and Support³	3-year limited hardware warranty and 8x5 phone, web and email support	
Standard Service	3-year limited hardware warranty and 8x5 phone, web and email support	
Upgrade/Extension Options	Replacement part dispatch on the next business day (up to 5 years) Advanced Service: 24x7 phone, web and email support + onsite diagnostics on the next business day (up to 5 years) Premium Service: 24x7 phone, web and email support + onsite diagnostics in 4 hours (up to 5 years) Extended Standard Service up to 5 years	

¹ Please refer to corresponding models for the supported drives of expansion enclosures.

² For detailed dimensions, please visit the Infortrend website.

³ All EonStor DS systems are shipped with Standard Service.

* All design and specification declared are subject to change without notice in advance. All rights reserved. Please refer to Infortrend website for further information or localization updates.

Infortrend
Infortrend Technology, Inc.

Asia Pacific (Taipei, Taiwan)
Infortrend Technology, Inc.
Tel: +86-2-2226-0126
E-mail: sales.ap@infortrend.com

China (Beijing, China)
Infortrend Technology, Ltd.
Tel: +86-10-6310-6168
E-mail: sales.cn@infortrend.com

Japan (Tokyo, Japan)
Infortrend Japan, Inc.
Tel: +81-3-5730-6551
E-mail: sales.jp@infortrend.com

Americas (Sunnyvale, CA, USA)
Infortrend Corporation
Tel: +1-408-988-5088
E-mail: sales.us@infortrend.com

EMEA (Basingstoke, UK)
Infortrend Europe Ltd.
Tel: +44-1256-305-220
E-mail: sales.eu@infortrend.com