

Dot Hill 2722

Entry-Level Fibre Channel storage array



Built in Redundancy

- RAID 0, 1, 3, 5, 6, 10, 50
- Redundant, hot swap components
- AssuredSnap™ - Optional snapshot capability
- AssuredCopy™ - Additional data protection with full volume copies
- Built-in schedule capability

Scalability and Performance

- Dual or single RAID controller or JBOD
- Data rates of 4Gb/sec. (Fibre Channel)
- OS Support - Windows, Linux, Solaris
- Modular design protects your investment
- Enterprise-class features and functionality without the enterprise price

Environmentally Responsible / Lower TCO

- EcoStor™ - Economically and environmentally sound technologies
 - SimulCache™ - Low latency cache mirroring
 - Battery-free cache backup
 - DC power option
- RoHS-6 and WEEE compliant

Flexible and Scalable SAN Array

The 2722 features a 24-drive hardware RAID storage array housed in a 2 rackunit (2U) enclosure providing dual 4Gb Fibre Channel interfaces per controller to internal 2.5 inch disk and solid state drives. The 2722 is a natural evolution of the world-class Dot Hill 2000 Series product family, adding support for the emerging 2.5 inch enterprise disk technology to deliver higher IOPS performance in a 2U rack size and shorter chassis depth of under 600mm including cable bends. An internal SAS interface will support up to six additional drive enclosures with 3.5" SAS or SATA drives or three additional enclosures with 2.5" SAS or SATA drives. With support for a total of 96 attached drives managed by the Dot Hill R/Evolutionary RAID architecture, the 2722 adapts to a broad range of business and mission-critical applications including databases, business analysis, video streaming and email.

Revolutionary connectivity, availability, quality and value

The 2722 uses revolutionary SimulCache™ technology that instantly and simultaneously mirrors cache between RAID controllers, leading to significant performance improvements over traditional implementations. The use of RAID cache batteries has been completely eliminated with the introduction of super capacitors, providing infinite cache backup during a power loss while being environmentally friendly. AssuredSnap™ provides the 2722 with built-in volume snapshot capability allowing point-in-time copies that can be used to maximize business continuity. AssuredCopy™ creates a full volume copy (vs. a logical volume copy with AssuredSnap) providing additional protection against vdisk failure and eliminating application I/O contention when accessing the same data blocks.

Storage made easy

The 2722 is easy to configure and manage with improved RAIDar 2.0, the intuitive Web Based Interface (WBI) which provides storage setup and monitoring without the need for host based software.

Dot Hill 2722 specifications

■ GENERAL

Product Family	2002 Series
Product Type	RAID, JBOD
Chassis Configuration	2U
Disk Architecture	3Gb SAS
Max Drives per Chassis	24 drives
Total Disks Supported	96
Mounting Options	19" Rack, Rack tray
Max Number of Chassis	7 (1 RAID and 6 JBOD)
Max Capacity per Chassis	7.2TB
Data Management Services (DMS)	AssuredSnap™, AssuredCopy™

■ PROTOCOLS AND STANDARDS

IP (RFC, 894, 1092)	SCSI-2 and SCSI-3
---------------------	-------------------

■ HOSTS

Supported Hosts	Up to 4 direct connected hosts, 2 or 4Gb Fibre Channel
Interface Type	FCP
External Ports	2 Single or 4 Dual Controller

■ DRIVES

Max Number of Drives	96
Drive Options	SAS 36GB 15K RPM SAS 72GB 15K RPM SAS 146GB 10K RPM SAS 300GB 10K RPM SATA 32GB SSD SATA 64GB SSD SATA 80GB SSD SATA 160GB SSD

■ RAID

Levels Supported	Non-RAID, 0, 1, 3, 5, 6, 10 and 50
RAID Type	Hardware
Cache Memory	1GB per controller
Cache Backup	Battery-free protection with super capacitors
Virtual disks per System	32
Volumes per virtual disk	256
Volumes per System	256
Mirrored Cache	Yes - SimulCache™
Super Capacitor Cache Backup	Yes
Cache Backup to Flash	Yes - Non-volatile

■ MANAGEMENT

Interface Types	Mini DB9 RS232, 10/100 Ethernet
Protocols Supported	SNMP, SSL, SSH, SMTP, SMI-S Provider, HTTP(S)
Management Consoles	WEB GUI, CLI
Management Software	RAIDar 2.0

■ POWER REQUIREMENTS - AC INPUT

Input Power Requirements	100-240VAC 50/60Hz 4.5-1.9A
Max Input Power	436W maximum continuous
Heat Dissipation	1488 BTUs/hour

■ POWER REQUIREMENTS - DC INPUT

Voltage	-34 to -72VDC, -48/-60V nominal
Max Input Power	436W maximum continuous
Heat Dissipation	1488 BTU/hour

■ TEMPERATURE AND HUMIDITY RANGES

Operating Temperature	41°F to 104°F (5°C to 40°C)
Shipping Temperature	-40°F to 158°F (-40°C to 70°C) Note: Derate 2°C for every km, up to 3000 meters
Operating Humidity	10% to 90% RH @ 104°F (40°C), non-condensing
Non-Operating Humidity	Up to 93% RH @ 104°F (40°C) non-condensing

■ DECLARED ACOUSTIC NOISE LEVELS

Sound Power	<6.75B Sound Power
Sound Pressure	<55dBA Sound Pressure

■ SHOCK AND VIBRATION

Shock, Operational	5.0G, 10ms, half sine
Shock, Non-Operational	15G 11ms, half sine
Vibration, Operational	0.21Grms Random 5Hz to 500Hz flat spectrum/feed forward
Vibration, Non-Operational	0.5G 1 octave/minute 5Hz to 500Hz to 5 Hz sine sweep 0.5Grms Random 20Hz to 1000Hz flat spectrum

■ HIGH-AVAILABILITY FEATURES

Redundant Hot-Swap Controllers	Yes
Redundant Hot-Swap Disk	Yes
Redundant Hot-Swap Fans	Yes
Redundant Hot-Swap Power	Yes
Dual Power Cords	Yes
Hot Standby Spare	Yes
Automatic Failover	Yes
Multi-Path Support	Yes
Snapshot with AssuredSnap™	Yes
Volume Copy with 2722™	Yes

■ REGULATORY

Safety	UL 60950-1:2001 (USA) CAN/CSA-C22.2 No.60950-1-03 (Canada) EN 60950-1 :2001 (EU) IEC 60950-1 :2001 (International)
Electromagnetic Compatibility Emissions	CFR 47 Part 15 Subpart B Class A (USA) IECS-003: 2004 Class A (Canada) AS/NZS CISPR 22: 2006 Class A (Australia/New Zealand) VCCI: 2008-4 Class A EN 55022: 2006 Class A (European Union)
Harmonics Flicker	EN 61000-3-2: 2006 EN 61000-3-3: 1995 (Amended by A1: 2001 and A2: 2005)
Immunity	EN 55024: 1998 (Amended by A1: 2001 and A2: 2003)Electromagnetic Compatibility
RoHS and WEEE	RoHS-6 Compliance , China RoHS, WEEE
Country Approvals	Australia/New Zealand, Canada, European Union (EU), Germany (GS Mark), Japan,United States

■ SUPPORT

Software Warranty	90 days
Standard Hardware Warranty	3 years
Environmental Monitoring	SNMP, CLI, RAIDar 2.0, SMTP, SMI-S Provider
Phone-home Capability	Yes
Remote Diagnostics	Yes
Non-disruptive Updates	Yes
Non-disruptive Volume Expansion	Yes for primary volumes and snapshot volumes

■ PHYSICAL

Height	3.5 Inches / 8.9cm
Depth (excluding cables)	21.3 Inches / 54.0 cm
Width	17.6 Inches / 44.7cm
Chassis Weight	44 lbs / 20kg
Chassis (w/148GB drives) Weight	58 bs / 26.4kg

Specifications are subject to change at any time.

